

NAME

freetype-config — show information about installed freetype2 libraries

SYNOPSIS

freetype-config [**--prefix**] [**--prefix=PREFIX**] [**--exec-prefix**] [**--exec-prefix=EPREFIX**]
[**--version**] [**--ftversion**] [**--libs**] [**--libtool**] [**--cflags**]

DESCRIPTION

This manual page documents briefly the **freetype-config** command,

freetype-config is a program that shows information about the installed freetype2 libraries.

OPTIONS

The following options are supported:

--prefix **--prefix=PREFIX**

Show the prefix freetype2 was built with. The prefix may be overridden by passing the argument PREFIX.

--exec-prefix **--exec-prefix=EPREFIX**

Show the executable prefix freetype2 was built with. The executable prefix may be overridden by passing the argument EPREFIX.

--version Show the libtool version of the installed freetype2.

--ftversion

Show the FreeType version of the installed freetype2.

--libs Show the compiler flags for linking to the installed freetype2.

--libtool Show the library name for linking with libtool.

--cflags Show the compiler flags for compiling against the installed freetype2.

AUTHOR

This manual page was written by #USERNAME# will@debian.org for the **Debian** system (but may be used by others). Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts and no Back-Cover Texts.