

**NAME**

`libart2-config` – script to get information about the installed version of `libart 2.x`

**SYNOPSIS**

`libart2-config` [ `--prefix[=DIR]` ] [ `--exec-prefix[=DIR]` ] [ `--libs` ] [ `--cflags` ] [ `--version` ]

**DESCRIPTION**

**libart2-config** is a tool that is used to determine the compiler and linker flags that should be used to compile and link programs that use *libart* library.

**OPTIONS****--prefix=PREFIX**

If specified, use *PREFIX* instead of the installation prefix that *libart* was built with when computing the output for the **--cflags** and **--libs** options. This option is also used for the exec prefix if **--exec-prefix** was not specified. This option must be specified before any **--libs** or **--cflags** options.

**--exec-prefix=PREFIX**

If specified, use *PREFIX* instead of the installation exec prefix that *libart* was built with when computing the output for the **--cflags** and **--libs** options. This option must be specified before any **--libs** or **--cflags** options.

**--libs** Print the linker flags that are necessary to link a *libart* program.

**--cflags** Print the compiler flags that are necessary to compile a *libart* program.

**--version**

Print the currently installed version of *libart* on the standard output.

**AUTHOR**

This manual page was written by Christian Marillat <marillat@debian.org> for the Debian GNU/Linux system (but may be used by others).