

NAME

unrar – extract files from rar archives

SYNOPSIS

unrar <command> [-<switch 1> -<switch N>] archive [files...] [path...]

DESCRIPTION

This manual page documents briefly the **unrar** command.

This manual page was written for the Debian GNU/Linux distribution because the original program does not have a manual page.

Commands and options described here are as of unrar 2.02.

OPTIONS

After the program name comes a command and then optional switches with dashes before them. A summary of commands is included below. For a complete description, run **unrar** without options.

- e** Extract files to current directory.
- l** List archive content.
- p** Print file to stdout.
- t** Test archive files.
- v** Verbosely list archive.
- x** Extract files with full path.

SWITCHES

NOTE: Every switch must be separated by a whitespace. You cannot put them together.

- av-** Disable AV check.
- c-** Disable comments show.
- f** Freshen files.
- kb** Keep broken extracted files.
- ierr** Send all messages to stderr.
- inul** Disable all messages.
- o+** Overwrite existing files.
- o-** Do not overwrite existing files.
- p<password>**
 Set password.
- p-** Do not query password.
- r** Recurse subdirectories.
- u** Update files.
- v** List all volumes.
- x<file>**
 Exclude specified file.
- x@<list>**
 Exclude files in specified list file.
- x@** Read file names to exclude from stdin.
- y** Assume Yes on all queries.

AUTHOR

This manual page was written by Petr Cech <cech@debian.org> according to "unrar -h" for the Debian GNU/Linux system (but may be used by others).